



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Splitex Justagekleber Aktivator

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Application of the substance / the preparation: Auxiliary for dental technology

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Amann Girrbach AG
Herrschaftswiesen 1
A-6842 Koblach
Telefon: +43 5523 623330
Fax: +43 5523 55990
Email: austria@amanngirrbach.com
Internet: www.amanngirrbach.com

Further information obtainable from: Amann Girrbach GmbH

1.4 Emergency telephone number:

Giftinformationszentrum-Nord / GIZ-Nord Poisons Centre
Telefon / Phone +49 (0) 551/19240
24h / 7d

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008:



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1 H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2 H351	Suspected of causing cancer.
STOT RE 2 H373	May cause damage to the respiratory tract through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315	Causes skin irritation.
Eye Irrit. 2 H319	Causes serious eye irritation.
Skin Sens. 1 H317	May cause an allergic skin reaction.
STOT SE 3 H335	May cause respiratory irritation.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 1)

Hazard pictograms:

GHS02 GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues

Hazard statements:

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to the respiratory tract through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards:**Results of PBT and vPvB assessment:****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	>25-≤50%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26	Reaction products of phosphoryl trichloride and 2-methyloxirane ⚠ Acute Tox. 4, H302	>10-≤25%

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 2)

CAS: 115-10-6	dimethyl ether	>2.5-≤10%
EINECS: 204-065-8	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119472128-37		
CAS: 74-98-6	propane	>2.5-≤10%
EINECS: 200-827-9	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 75-28-5	isobutane	>2.5-≤10%
EINECS: 200-857-2	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures:

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

After inhalation: Supply fresh air; consult doctor in case of complaints.**After skin contact:** In cases of frost bites, rinse with plenty of water. Do not remove clothing.**After eye contact:**

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing: Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed:

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing agents:CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture:** Can form explosive gas-air mixtures.**5.3 Advice for firefighters:****Protective equipment:**

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.**6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.**6.4 Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Do not spray onto a naked flame or any incandescent material.
Fumes can combine with air to form an explosive mixture.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities:**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
Store only in the original receptacle.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters:**Ingredients with limit values that require monitoring at the workplace:****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

8.2 Exposure controls:**Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands: Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 4)

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties:****General Information:****Appearance:**

Form:	Aerosol
Colour:	Beige
Odour:	Ether-like
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition:

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.

Flash point: Not applicable, as aerosol.**Flammability (solid, gas):** Not applicable.**Decomposition temperature:** Not determined.**Auto-ignition temperature:** Product is not selfigniting.**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

Lower:	0.4 Vol %
Upper:	32.0 Vol %

Vapour pressure: Not determined.**Density at 20 °C:** 1.0 g/cm³**Relative density:** Not determined.**Vapour density:** Not determined.**Evaporation rate:** Not applicable.**Solubility in / Miscibility with water:**

Not determined.

Partition coefficient: n-octanol/water: Not determined.**Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

Solvent content:**VOC (EC)** 15.9 %**9.2 Other information:** No further relevant information available.**SECTION 10: Stability and reactivity****10.1 Reactivity:** No further relevant information available.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 5)

10.2 Chemical stability:**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: Forms explosive gas mixture with air.**10.4 Conditions to avoid:** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide**SECTION 11: Toxicological information****11.1 Information on toxicological effects:****Acute toxicity** Based on available data, the classification criteria are not met.**Primary irritant effect:****Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity**

Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to the respiratory tract through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity:****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability:** No further relevant information available.**12.3 Bioaccumulative potential:** No further relevant information available.**12.4 Mobility in soil:** No further relevant information available.**Additional ecological information:****General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment:**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects:** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods:****European waste catalogue:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 6)

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number:**

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name:

ADR

1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

IMDG, IATA

AEROSOLS

14.3 Transport hazard class(es):

ADR

**Class:**

2 5F Gases.

Label:

2.1

IMDG, IATA**Class:**

2 Gases.

Label:

2.1

14.4 Packing group:

-

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user:

Warning: Gases.

EMS Number:

F-D,S-U

Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ):

1L

Transport category:

2

Tunnel restriction code:

D

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category**

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to the respiratory tract through prolonged or repeated exposure. Route of exposure: Inhalation.

Training hints:

Employees who use the product have to be trained on risks for health, hygiene, use of individual protection, accident preventive actions, rescue actions, etc.,

Department issuing SDS:

ADEEGO GmbH

Wildsteig 4A

D-42113 Wuppertal

Tel. +49 (0) 202 2575700

Fax. +49 (0) 202 2575701

Email: mail@adeego.de

www.adeego.de

Contact: Dr. Axel Deeg**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date: 05.02.2019

Revision: 05.02.2019

Trade name: Splitex Justagekleber Aktivator

(Contd. of page 8)

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
